

Basic technical parameters MMC

| BED AND GANTRY TYPE | | MMC 1500 POWER PLUS | MMC 1500 POWER | MMC 1500 SPEED | MMC 1500 SPRINT | MMC 1500 RAPID |
|---|----------------------|---------------------|----------------|------------------|-----------------|----------------|
| Spindle speed range | (min ⁻¹) | 20 ÷ 8000 | 20 ÷ 10000 | 20 ÷ 12000 | 20 ÷ 18000 | 20 ÷ 24000 |
| Spindle taper | | ISO 50 (HSK-A100) | ISO 50 | ISO 40 (HSK-A63) | HSK-A63 | HSK-A63 |
| Clamping surface | (mm) | 1500 x 1300 | 1500 x 1300 | 1500 x 1300 | 1500 x 1300 | 1500 x 1300 |
| Slide travel in the X axis | (mm) | 1500 | 1500 | 1500 | 1500 | 1500 |
| Table travel in the Y axis | (mm) | 1300 | 1300 | 1300 | 1300 | 1300 |
| Slide travel in the Z axis | (mm) | 600 | 600 | 600 | 600 | 600 |
| Max. weight on table | (kg) | 2500 | 2500 | 2500 | 2500 | 2500 |
| Dimension of the table clamping area - DT | (mm) | 720 x 1000 | 720 x 1000 | 720 x 1000 | 720 x 1000 | 720 x 1000 |
| Table travel in the X axis - DT | (mm) | 1500 | 1500 | 1500 | 1500 | 1500 |
| Cross beam travel in the Y axis - DT | (mm) | 1000 | 1000 | 1000 | 1000 | 1000 |
| Slide travel in the Z axis - DT | (mm) | 600 | 600 | 600 | 600 | 600 |
| Maximum table loading - DT | (kg) | 2500 | 2500 | 2500 | 2500 | 1250 |

The manufacturer reserves the right to change the product parameters and design without prior notice.

