


# MILLING MACHINES

## BED AND GANTRY TYPE



BED AND GANTRY TYPE		MMC 1500 POWER PLUS	MMC 1500 POWER	MMC 1500 SPEED	MMC 1500 SPRINT	MMC 1500 RAPID
Spindle speed range	(rpm)	20 ÷ 8000	20 ÷ 10000	20 ÷ 12000	20 ÷ 18000	20 ÷ 24000
Spindle taper		ISO 50 (HSK-A100)	ISO 50	ISO 40 (HSK-A63)	HSK-A63	HSK-A63
Clamping surface	(mm)	1500 × 1300	1500 × 1300	1500 × 1300	1500 × 1300	1500 × 1300
Slide travel in the X axis	(mm)	1500	1500	1500	1500	1500
Table travel in the Y axis	(mm)	1300	1300	1300	1300	1300
Slide travel in the Z axis	(mm)	600	600	600	600	600
Max. weight on table	(kg)	2500	2500	2500	2500	2500
Dimension of the table clamping area- DT	(mm)	720 × 1000	720 × 1000	720 × 1000	720 × 1000	720 × 1000
Table travel in the X axis- DT	(mm)	1500	1500	1500	1500	1500
Cross beam travel in the Y axis- DT	(mm)	1000	1000	1000	1000	1000
Slide travel in the Z axis- DT	(mm)	600	600	600	600	600
Maximum table loading- DT	(kg)	2500	2500	2500	2500	1250

